

Specification	Move SE	Move 4K	
Photo			
Camera Model	Move SE 12x Move SE 20x Move SE 30x	Move 4K 12x Move 4K 20x	
Camera Dimensions (WxDxH)	12x, 20x, 30x 142 mm x 169 mm x 164 mm	12x and 20x 168.4 mm x 141.5 mm x 164.5 mm	
Recommended Model	 D2-CD-PTZO D2-CD-HB-PTZO	 HD12-CD-PTZO HD12-CD-HB-PTZO	
Cooling	The "CD" refers to the cooler inside the housing. The cooler is thermostatically controlled by a preprogrammed thermostat. The cooler turns on at 95° F to begin the cooling process. The cooler resets at 80° F.		
Heating	The "HB" refers to the heating element inside the housing. The heater will turn on at 50° F. The thermostat will then reset at 70°F. The heating element for all models start at 25 watts each. Additional heating elements can be added for colder climates.		
Fans	The interior fan is always on to circulate airflow. The external fan acts to remove the excess high heat from inside the housing. The external fans turn on with active cooling at 95° F. They will then reset at 70° F.		
Camera Sled (Included)			
Standoff Configuration	STANDOFF CONFIGURATION WILL GO HERE		
Step Down Power Supplies	Indoor Included standard is the indoor 12v power supply. 	Outdoor Optionally, you can upgrade the indoor power supply with an outdoor 12v power supply or our KT-CDR2-AC. This powered mounting bracket provides the necessary 12v power and mounting solution. 	Outdoor 12v outdoor power supply is included, known as the KT-CDR2-AC. The KT-CDR2 powered mounting bracket provides the necessary 12v power and mounting solution.

INCLUDED

Camera Accessories To Fit Your Unique Install Needs

Specification	Pole Mount	Ceiling Mount	Corner Mount	Ceiling Mount SS
Photo				
Part Name	BR-MPM1	BR-CM1	BR-CNR2	BR-ASM3