

Versatile, Virtually Indestructible and Ready for the Extreme

Dotworkz takes vandal protection to new levels with the 2012 KT-Shield Ballistic Armor Shield. Our bullet-resistant cover package protects cameras and sensitive internal equipment against small-arms fire and intense vandalism using a two-part energy absorption solution. Heavy stainless steel and virtually indestructible thermoplastic create a protection system tough enough for the most hazardous of deployments.

The KT-Shield protects up to 9 millimeter and 45 caliber fire, meeting UL 750 Level 1 Ballistic Protection Standards.



innovative

KT-SHIELD: Dotworkz D2 KT-Shield Ballistic Armor



Features:

- Stainless Steel Protective covering for D2 Series Housings
- Available in 0.22 Cal Resistant, 16gg Stainless Steel
- Available in 0.38 Cal, 9mm resistant 10gg* Stainless Steel
- Equipped with Vandal Resistant Closure Screws (standard)
- Custom painting to fit specific project requirements*
- Available for several D2 environmental enclosures, including HB-MVP, TR-MVP, COOLDOME, RF-MVP, HB-Solar, & BASE models
- Ideal for Industrial, Marine, Government, and Commercial Security deployments requiring ballistic tough Housings

Description:

Dotworkz KT-Shield Ballistic Armor is the most durable protection solution to date. Engineered with dual energy absorption system of heavy gage stainless steel and virtually indestructible thermoplastic, the KT-Shield protects against small arms fire up to 9mm and 45 caliber ranges* and all forms of vandalism.

The IK10 rated Dura View lens and Vandal Resistant Closure Screws are standard in the Mark IV Ballistic Armor, and provide the highest rate of protection possible for sensitive cameras and electronic equipment.

Specs:

Stainless Steel Gauge:

16gg - 0.22 Cal Resistant (Standard)

10gg - 0.38 Cal & 9mm Resistant (Special Order)

Available for the Following D2 Enclosures:

HB-MVP, TR-MVP, RF-MVP, HB-SOLAR, CD, BASE

Color:

Powder Coated White, Black, or polished

Stainless Steel Metal

Shipping Weight:

20lbs (9.07kg)
Shipping Dimensions:

17" x 13" x 16"





remote video solutions