

Architectural & Engineering Specifications (A & E)

S-Type Camera Housing with Ring of Fire. Vandal Resistant Camera Housing Compatible with Box / Brick Style Cameras.

PRODUCTS

1.00 MANUFACTURER


- A. Dotworkz, Inc.
3688 Midway Drive
San Diego, CA 92110
PH. +1 (866) 575-4689
FAX +1 (619) 639-9914
- B. This product shall be manufactured in the USA using the highest quality.

1.02 GENERAL CAMERA ENCLOSURE DESCRIPTION

- A. Camera Enclosure for box style cameras, with specified shall be designed for Ethernet networks and Analog Systems for commercial, industrial, or government applications requiring a rugged, sealed outdoor rated camera enclosure with compatibility to house a broad range of fixed brick style cameras commercially available for on Analog/ CCTV, IP, and High Definition, and Megapixel capability.
- B. Camera Enclosure shall be built to withstand elements to provide camera protection to a rating of IP66 and/or NEMA 4X standard.
- C. Housing shall be built to be vandal resistant using heavy duty, thermally stable, & shatter resistant Polycarbonate Thermoplastic.
- D. Housing shall be fully Sealed and Suitable for Deployments into a broad range of environments, including Commercial, Industrial, Marine, Fine Dust Particulate, Humid or Dry, and in Indoor or Outdoor Environments.
- E. Shall include two IP68 wire ports provided for power & data cabling entry.

ST-RF-MVP Outdoor Housing

Dotworkz S-Type Enclosure with Ring of Fire Specifications & Multi-Volt Platform



1.03 CAMERA ENCLOSURE REQUIREMENTS

- A. Shall be an environmentally sealed Polycarbonate thermoplastic housing built to withstand water and dust to an IP rating of IP66.
- B. Shall be compatible with a large variety and brands of fixed, Brick style IP and Analog camera systems.
- C. Shall include integrated 65 watt, thermostatically controlled Heaters that surround inside of housing for protecting camera from extreme cold & provide enclosure de-icing capability Ring of Fire version
- D. Shall have two integrated 10 CFM fan blowers; always On, for a total of 20 CFM fan cooling & thermal protection. Shall include environmental control board for providing power management to thermal protective elements which include a heater and fan, and provide power to a 12VDC camera, or power a 24 V camera or accessory. Shall provide Wall Mounting Bracket, with capacity to bolt enclosure to wall, with manually adjustable pan angle and tilt angle to housing.
- G. Wall mounting bracket shall have an optional capacity to pole mount, via pole mounting bracket accessory, sold separately. Shall be compatible with a media connection cable of Category 5 and/or Category 5 Enhanced and/or Category 6 twisted pair (UTP) cable, using RJ45 compliant connectors.
- I. Wire ports provided shall be compatible with analog coaxial media connection data cable, and seal to a rating of IP68 or better.
- J. Enclosure's viewing window shall be optical grade clear Lexan polycarbonate.



2.00 Electrical Specification

- A. Enclosure shall have integrated capacity to be universally powered by 95-264 VAC single phase Power, or by 20-30 VAC/ VDC to be compatible with both high & low voltage powering standards in one model.
- B. Each MVP Enclosure model shall provide Voltage available to power Cameras of 12VDC & 24V of 26 watts total, integrated into MVP power chassis, with user accessible camera power hook-up.
- C. Shall have integrated dual high flow blower fans for 20 CFM air movement.
- D. Shall have integrated thermostatically controlled 65 watt internal heaters surrounding interior of enclosure & protecting camera from cold.
- E. Shall include one camera powering cable for quick camera powering hook-up.
- F. Shall have integrated safety fusing on All Camera Power outputs.
- G. Shall have integrated safety fusing on Integrated Blower fans.

2.01 Mechanical Specifications - Housings

- A. Weight: 7 lbs (3.2 kg) for Enclosure & Wall Mount Arm, Ring of Fire Model.
- B. Exterior 21.0(L) x 5.4(H) x 7.4(W) (without Mounting Arm).
- C. Interior 13.0(L) x 3.75(H) x 5.0(W) (cam. install area avail.).
- D. Hinged Top with Captive Stainless Steel Fasteners.
- E. Rugged Polycarbonate Housing (.195" /5mm wall).
- F. Clear Lexan Polycarbonate Viewing Window 3.10"H x 3.65"W x 0.118"gg.
- G. White Semi-gloss finish.
- H. Protective Urethane Gasket Seals.

2.02 Mechanical Specifications - Mounting Arm

- A. Shall include Heavy Duty "Strong-Arm" Cast Aluminum Wall mount Arm and include Stainless Steel hardware to mount Arm to S-Type Enclosure.
- B. Mounting Arm Shall have a matching White Powder Coat finish.
- C. Provided Mount Arm Shall have Integrated PAN & TILT adjustment Capacity.
- D. All Mounting Arms Shall have capacity for Wall mounting of enclosure.
- E. Dotworkz Shall have available an optional capacity to pole mount, via optional EZ-Lock Pole Mount Bracket #BR-MPM1, sold separately.

2.03 Environmental Specifications

- A. Recommended Operating Temperature Range: -50°F to 122°F (-46°C to 50°C)
- B. Absolute Operating Temperature Range -50°F to 140°F (-46° to 60°C)
- C. Shall operate in a Humidity: 10% to 90% non-condensing.
- D. Shall be built to a standard rating of NEMA 4X and/or IP66.
- E. Shall provide two IP68 seals cable gland ports for power and data cables.